



Yolo County Community Services Department

Environmental Health Division
292 W. Beamer Street, Woodland, CA 95695
Phone (530) 666-8646 Fax (530) 669-1448

MONITORING WELL PERMIT CONDITIONS

Permit#: _____ FA#: _____ WP#: _____

Facility Name/Location: _____

Description of Work: _____

This permit expires 365 days from date of issue.

- Well Installation:** Sanitary seal inspection required*
 - Tremie Placement Required.
 - Concrete Pad (Min 2 X 2 Feet) Required For Installations Not Into Paved Surfaces.
 - Neat Cement Slurry Required.
- Soil Boring/ Hydropunch/ Cone Penetrometer/ Borehole:** Destruction inspection required*
 - Tremie Placement Required.
 - Neat Cement Slurry Required.
- Well Destruction:** Destruction inspection required*
 - Tremie Placement Required.
 - Pressure Grout Placement.
 - Neat Cement Slurry Required.
 - Over Drill and Remove Casing.

Note: Neat Cement Slurry is at least one 94 pound bag Portland cement to 4.5 to 6.5 gallons of water. Bentonite may be added but only between 3% and 5% by weight of the dry materials.

DRILL CUTTINGS AND PURGE WATER STORAGE: Potentially hazardous waste to be appropriately labeled and stored per CCR Title 22 and DOT requirements and properly secured until analytical results determine appropriate disposal options.

HAZARDOUS WASTE DISPOSAL: Drill cuttings, purge water or other materials found to meet hazardous waste criteria must be disposed of as hazardous waste within 90 days of generation. Other contaminated wastes must be disposed of as approved by Yolo County Environmental Health. Non-contaminated waste must be disposed of as solid waste.

REPORTING REQUIREMENTS:

- Provide as-built site map of installation/destruction required.
- Report of installation, sampling, and analytical finding required within 60-days of drilling.

OTHER: You are required to give at least 48 hour notice prior to grout inspection.

CALL (530) 666-8646 TO SCHEDULE INSPECTIONS